

Product information

Bomo-Flex-NL

Application:	Bomo-Flex–NL is a thermally transferable polyurethane film with special heat sealing adhesive for labeling of hydrophobic and water-repellent nylon fabrics. By laminating a transparent self-adhesive PET film Bomo-Flex- NL guarantees excellent cutting and weeding characteristics. The raw materials are ecologically harmless and free of PVC plasticizers or heavy metals (in accordance with Oeko-Tex Standard 100).			
Resistance:	Washable up to 40 °C. Wash textile inside out. Do not use softener and dryer			
Transfer:	material	temperature	time	pressure
	Nylon	150 °C	press for 4 sec pull off polyester carrier lukewarm repress for 10 sec	2.0 bar
Colors:	black, white, yellow, red, orange, grey, light blue, green, gold metallic, silver metallic			
Dimensions:	roll width roll length	50 cm 25 lfm		
Comment:	This information is intended as a guideline for the application. Depending on the materials used, the transfer parameters must be adjusted accordingly. The information is based on the current technical standard.			

1/1

VELOURDECOR · FIBRE-WALL · BOMOPRINT

Borchert + Moller GmbH & Co.KG • Flock- u. Drucktechnik, Wandbeläge • Kreuzäckerstraße 11-13 • D-72401 Haigerloch-Stetten Telefon +49-(0)7474-9565-0 • Telefax +49-(0)7474-9565-35 • e-mail: info@borchert-moller.de •www.borchert-moller.de •HRA 548