

Borchert + Moller GmbH & Co.KG • Kreuzäckerstraße 11-13 • D-72401 Haigerloch - Stetten

Product Information

Bomo-Flex Print Opak NEW

PU – transfer film for solvent and Eco solvent printer with block-out coating

Subsurface:

Bomo-Flex Print Opak NEW is used for motifs and logos on sport, leisure and work wear.

Bomo-Flex Print Opak NEW is a heat-sealable, printable PU textile transfer film (opaque white) suitable for applications on light and dark fabrics as well as sublimated polyester. Not suitable for heat transfer are textiles that have a water-repellent finish or impregnation.

We recommend using *Bomo-Flex Tape* as a transfer tape and as a protection cover during the heat transfer.

Transfer requirement

Temp: 140 - 145 °C Time: 10 sec Pressure: medium

The PET liner should be removed lukewarm

Wash resistance

Washable up to 40 °C

- Only color or mild detergent
- Wash textiles inside out
- Not suitable for dryer

Printing

-True sided

Particular feature

Wash textile not before 48 hours after printing.

For larger, coherent designs starting from approx A5 size, the washing resistance may deteriorate. Therefore, we recommend to carry out appropriate washing tests

The technical specifications rest on extensive tests and technical research. Due to the variety of possible influences during refinement, and use, the specifications should be viewed as reference values. We recommend a suitability test on the original material. A legally binding warranty of specific characteristics cannot be derived from our specifications.

VELOURDECOR · FIBRE-WALL · BOMOPRINT